



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
04.08.2004 Bulletin 2004/32

(51) Int Cl.7: **G06F 17/50, G06F 17/60**

(21) Application number: **02770266.1**

(86) International application number:
PCT/JP2002/011081

(22) Date of filing: **25.10.2002**

(87) International publication number:
WO 2003/038688 (08.05.2003 Gazette 2003/19)

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR
Designated Extension States:
AL LT LV MK RO SI

- **UEDA, Masami**
Kakogawa-shi, Hyogo 675-0034 (JP)
- **NISHI, Koichiro**
Kakogawa-shi, Hyogo 675-0012 (JP)
- **OKAMOTO, Kenzo**
Kobe-shi, Hyogo 651-1212 (JP)
- **YASUI, Takao**
Kakogawa-shi, Hyogo 675-0103 (JP)

(30) Priority: **29.10.2001 JP 2001331126**

(71) Applicant: **Kawasaki Jukogyo Kabushiki Kaisha**
Kobe-shi, Hyogo 650-8670 (JP)

(74) Representative: **Maxton Langmaack & Partner**
Patentanwälte,
Postfach 51 08 06
50944 Köln (DE)

(72) Inventors:
• **TANAKA, Shigetsugu**
Akshi-shi, Hyogo 674-0054 (JP)

(54) **PARTS CATALOGUE CREATION APPARATUS**

(57) In a part catalog creating system, a part table containing design change numbers respectively set for parts, and header numbers, part numbers, and quantity of the parts, each of which corresponds to the design change numbers, is created, and product number data that contains design change number of part used for manufacturing each product is created, and information

that coincides with the product number data is selected from the part table, thereby creating a product number list. The product number list and images of parts corresponding to the product number list are combined and the part catalog data for each product number is output. Thus, the part catalog can be easily created without errors.




Fig. 1

Description**Disclosure of the Invention****Technical Field**

[0001] The present invention relates to a part catalog creating system capable of creating catalogs of a plurality of parts composing a product obtained by assembling the plurality of parts.

Background of the Invention

[0002] When a customer purchases a product composed of a plurality of parts and prepares spares of expendable parts of the product, or the parts break down and hence should be repaired, the customer needs a part catalog in which part numbers are listed for the customer to order the parts.

[0003] In the case of products composed of a few parts, it is relatively easy to create a part catalog for each product. However, in the case of products, for example, robot products, which are composed of numerous parts, and are required to meet various requirements of customers, and to deal with constantly advancing performance of control parts or the like, in an extreme case, products designed differently with very small difference for each product, the parts vary from product to product. In such products, therefore, it is not easy to create the part catalogs of the parts. In the case of the robot product, part configuration in each robot manufactured based on the customers' requirements varies from customer to customer, and its design cycle is extremely short. Therefore, in order to meet the customers' requirements, it is necessary to frequently create part catalogs containing different contents in a short period, which requires enormous labor and cost.

[0004] For this reason, the part catalogs of the robot products are created for a representative product in special occasion, for example, in a time period when new products are placed on sale, and thereafter, after services such as revision associated with design change are hardly provided. That is, the catalogs are transiently created. More often than not, the contents of the catalogs become obsolete, and hence become unserviceable.

[0005] Conventionally, the part catalogs associated with the robot product are created by manually selecting parts of the product from total part list in which all the parts used to manufacture the robot product are listed. Regardless of change in the parts to be used according to design change, there arise problems that part numbers before change are listed by mistake, wrong part numbers are described because of posting error, or optional parts demanded by the customer are not listed.

[0006] Further, it is virtually difficult to create the part catalogs to have a one to one correspondence with the robot products designed differently for each robot as described above, in view of required labor and cost effectiveness.

[0007] The present invention provides a part catalog creating system comprising:

(a) a part table creating means including a first storage portion configured to store a part table to be rewritable, the part table containing design change numbers respectively set for a plurality of parts composing a product obtained by assembling the plurality of parts and information corresponding to the design change numbers;

(b) a product number data creating means including a second storage portion configured to store product number data containing design change numbers and information of parts used for each of product numbers of a product assembled with different part configurations so as to correspond to the product numbers;

(c) a judgment means configured to compare a design change number of the product number data of the product that has been read out from the second storage portion to a design change number of the part table that has been read out from the first storage portion, select the design change number of the part table that coincides with the design change number that has been read out from the second storage portion, and remove design change numbers remaining unselected and information corresponding to the unselected design change numbers from the part table; and

(d) a control means configured to create part catalog data for each product number of the product from the part table that contains the information corresponding to the design change number selected by the judgment means, and to output the part catalog data.

[0008] In accordance with the present invention, the judgment means compares the part table stored in the part table creating means to the product number data stored in the product number data creating means, and based on the design change number specified by the product number data, the part table corresponding to each product number of the product can be selected and created without human's labor. Therefore, the part table for each product number of the product can be created correctly and without a need for much labor, without errors in posting, missing of optional parts, etc.

[0009] So, in the case of the product, for example, a robot, which is composed of numerous parts, has a variety of part configurations according to the customers' requirements, and is designed in a short cycle, the part catalog having a one to one correspondence with the product can be created correctly and without much labor.

[0010] The part catalog creating system may further comprises

an image creating means configured to create an image corresponding to the design change number selected by the judgment means, wherein

the control means may be configured to create the part catalog data for each product number of the product, from the image created by the image creating means and the part table containing the design change number selected by the judgment means and information corresponding to the design change number, and to output the part catalog data.

[0011] In accordance with the present invention, the control means combines the part table selected by the judgment means with the image selected by the judgment means, and creates and output the part catalog data for each product number of the product. Thereby, the part catalog data including the image can be created so as to have a one to one correspondence with the product number of the product correctly and without much labor.

[0012] In the part catalog creating system, the information corresponding to the design change numbers which are stored in the first storage portion of the part table creating means may include header numbers, part numbers, and quantity (the number) of parts required to be assembled into the product,

the information stored in the second storage portion of the product number data creating means may include design change numbers of parts used for each product number of the product, header numbers of the parts, part numbers of the parts, and quantity (the number) of parts to be assembled into the product, and

the information corresponding to the unselected design change numbers removed from the part table by the judgment means may include header numbers, part numbers, and quantity (the number) of parts required to be assembled into the product.

[0013] In accordance with the present invention, the header number, the part number, and the quantity of parts required to be assembled into the product, each of which corresponds to the design change number, can be output as the part catalog data. Thereby, the part can be specified more easily

[0014] In the part catalog creating system, the part catalog data output by the control means may include a part name corresponding to the design change number.

[0015] In accordance with the present invention, the part catalog created from the part catalog data includes the part name corresponding to the design change number. Since individual parts can be specified by the part names in addition to the images, required parts can be specified more correctly.

[0016] In the part catalog creating system, the control means may create the part catalog data for each product number of the product from the part table that contains the design change number selected by the judgment means, the part number and the quantity of the parts required to be assembled into the product each of which corresponds to the design change number, and output

the part catalog data in such a manner that parts for standard equipment are distinguished from optional parts.

[0017] In accordance with the present invention, the optional parts equipped for each product number can be easily known, in addition to the parts for standard equipment, and preparation of the parts in the working station or the like is facilitated.

[0018] The part catalog creating system may further comprise:

a communication means configured to transmit the part catalog data output from the control means through a communication network, wherein the part catalog is searchable and accessible through the communication means.

[0019] In accordance with the present invention, the part catalog data for each product number which is output by the control means can be transmitted by the communication means through a communication network such as a public phone line. The communication network is realized by, for example, Internet. Customers, selling companies, and the like can search and access to the part catalog created for each product number which is transmitted through the communication means through terminals connected to the communication network.

[0020] In the part catalog creating system, the part catalog data output from the control means may be stored in an external storage medium to allow a part catalog to be delivered.

[0021] In accordance with the present invention, the part catalog stored in the external storage medium can be delivered to the customer together with the product. By delivering the part catalog stored in the storage medium, the customer does not confuse the product listed in the part catalog with the delivered product. In addition, with the part catalog corresponding to the delivered product, the customer can easily specify and order the required parts. Further, by storing the part catalog delivered together with the product, for example, in a storage portion provided in the product, missing of the part catalog can be avoided, and information relating to maintenance of the product can be easily obtained from the stored part catalog.

Brief Description of the Drawings

[0022]

Fig. 1 is a view showing a simplified configuration of a part catalog creating system according to an embodiment of the present invention;

Fig. 2 is a view showing an example of a part table;

Fig. 3 is a view showing an example of an output of optional part data stored in a second storage portion;

Fig. 4 is a view showing a distribution list image that provides an instruction on supply of parts to working sections;

Fig. 5 is a view showing an example of an output of a list for each robot number as a part table by a judgment means;

Fig. 6 is a view of an example of an image of a part catalog showing an apparatus construction of a robot;

Fig. 7 is a view showing an example of a content list portion of the part catalog relating to each assembly of the robot;

Fig. 8 is a view showing an example of the part catalog relating to an assembly of the robot;

Fig. 9 is a flow chart for explaining a creating operation of the part catalog in a part catalog creating system 1; and

Fig. 10 is a view showing a simplified configuration of a part catalog creating system according to a second embodiment of the present invention.

Best Mode for Carrying Out the Invention

[0023] Fig. 1 is a view showing a simplified configuration of a part catalog creating system 1 according to an embodiment of the present invention. The part catalog creating system 1 comprises a part table creating means 4 comprised of a first input means 2 configured to input design change number set for each of a plurality of parts composing a product obtained by assembling the plurality of parts, and header number, part number, part name and quantity (the number) of parts required to be assembled into the product, each of which corresponds to the design change number, and a first storage portion 3 that stores a part table containing the design change number, the header number, the part number, the part name, and the quantity of parts required to be assembled into the product, each of which is input with the first input means 2, such that the part table is rewritable, a product number data creating means 7 comprised of a second input means 5 configured to input a design change number of a part used for each product number of a product assembled with different part configurations, and header number, part number, and quantity (the number) of parts required to be assembled into the product, each of which corresponds to the design change number, and a second storage portion 6 configured to store the design change number input with the second input means 5 as corresponding to the product number of the product, a judgment means 8 configured to compare the design change number corresponding to the product number of the product which has been read out from the second storage portion 6 to the design change number of the part table that has been read out from the first storage portion 3, select only the design change number of the part table that coincides with the design change number read out from the second storage portion 6, and remove design change numbers re-

maining unselected, and header numbers, part numbers, and quantity of parts required to be assembled into the product, each of which corresponds to the unselected design change numbers, from the part table, an image creating means 9 configured to create an image of the part corresponding to the header number, and a control means 10 configured to combine the part table that contains the design change number selected by the judgment means 8, the header number, the part number and the quantity of parts required to be assembled into the product each of which corresponds to the design change number with the image corresponding to the header number selected by the judgment means 8, create and output part catalog data for each product number.

[0024] In this embodiment, a robot product will be described as an example of a product. Hereinbelow, how to create a part catalog of the robot product will be described. The robot product comprises an arm portion and a control portion. The arm portion and the control portion comprise members forming groups into which a plurality of parts are assembled. Herein, for the sake of convenience, the robot is called a product and the arm portion and the control portion are called control equipment. Each member composed of a plurality of parts and forming the group in a layer lower than the arm portion and the control portion is called an assembly.

[0025] The part table creating means 4 is included in a system (herein, "design management system") having a function to input, hold, and output information relating to items of all the parts composing the robot and part configuration of the assembly, and information such as item change in the parts associated with design change in the robot product. The part table creating means 4 is a processing circuit realized by a computer or the like in which a central processing unit (CPU) is mounted.

[0026] The first input means 2 may be realized by, for example, a key board, with which character such as text and numeric character, is input, or may be realized by a bar code reader configured to read information from a bar code representing information, such as the design change number, the header number, the part number, the part name, and the required number, each of which corresponds to each part, and input the information. In order to reduce input errors, it is preferred that the bar code is created in advance and the information is input by the bar code reader.

[0027] As the first storage portion 3, a storage component such as a random access memory, a flash memory, or a hard disc which is capable of rewriting a stored content, is used. The first storage portion 3 stores the part table that contains the design change number, and the header number, the part number, the part name, the quantity of parts, and the like, each of which is input with the second input means 2. The first storage portion 3 is rewritable. When the item of the part, configuration of the assembly, and the like are changed according to the design change in the robot product, the change is over-

written or additionally written according to the change input with the first input means, thereby changing the part table.

[0028] Thus, the part table can be corrected according to sequential design change in the robot product. Therefore, revised version of the part catalog described later can be easily created according to the corrected content of the part table. As a result, the part catalog is inhibited from becoming obsolete.

[0029] Fig. 2 is a view showing an example of a part table 11. The part table 11 is an example obtained by reading the content stored in the first storage portion 3 and output onto a paper. In Fig. 2, number represented by alphabet and numeric values listed in column of assortment code 12 is header number of part, number represented by combination of numeric values listed in column of item code 13 is part number, combination of text and numeric values listed in columns of item name (English) 14 and item name (Japanese) 15 represent part name 16, and numeric value listed in column of head count 17 represent quantity (the number) of parts. In this embodiment, the design change number is used to specify the part by the part table creating means 4, the robot number data creating means 7, and the judgment means 4 for creation of the part catalog, but is not listed in the part table and the part catalog.

[0030] In this embodiment, other information such as drawing number 18 and material of each part are input with the first input means 2, and stored in the first storage portion 3. These information also form the part table 11. Information relating to all the parts used for manufacturing the robot product, are stored in the part table creating means 4, as the part table, regardless of the type and robot number of the robot product.

[0031] The robot number data creating means 7 comprises a system (herein referred to as "production management and acquisition management systems") having a function to input and store information relating to items of optional parts to be added to parts for standard equipment, which are used for assembling the robot, based on the parts for standard equipment and customers' requirements, and a function to output an instruction for acquiring the parts required for assembling and supplying the parts (hereinafter referred to as "distribution") to the assembling working section, when the robot number of the robot to be actually manufactured is determined. The robot number data creating means 7 is a processing circuit realized by a computer in which a central processing unit (CPU) is mounted.

[0032] The second input means 5 is realized by the bar code reader and/or the key board. With the second input means 5, the design change number of the part for the standard equipment and the optional part, and the robot number set as corresponding to the robot to be manufactured, are input. By doing this, the robot number of the robot to be manufactured is associated with the design change numbers of the parts to be used in the robot.

[0033] As the second storage portion 6, the storage component such as the random access memory, the flash memory, or the hard disc which can rewrite its stored content is used, as in the first storage portion 3. The robot number of the robot to be manufactured and the design change number of the part to be used for manufacturing and assembling the robot are stored in the second storage portion 6 for each robot.

[0034] In this embodiment, since the design management system comprising the part table creating means 4 is connected to the production management and acquisition management system comprising the robot number data creating means 7 as shown in Fig. 1, data such as the header number, the part number, the part name, and the quantity of parts are extracted from the part table according to the design change number input with the second input means 5, and the header number, the part number, or the like corresponding to the design change number input with the second input means 5 are stored in the second storage portion 6.

[0035] Fig. 3 is view showing an example of an output of optional part data 21 stored in the second storage portion 6. Fig. 4 is a view of an image of a distribution list 22 that provides instruction on supply of parts to working sections. The customer requests a manufacturer to add the optional parts for improvement of performance or the like according to use of the robot product and environment where the robot is used. The optional part is input to and stored in the second storage portion 6 such that the optional part is distinguished from the part for standard equipment. Fig. 3 shows the example of the optional part data 21, which are the content read out from the second storage portion 6 and output onto a paper. In Fig. 3, assortment code 12 is header number, part number 13 is number of the part, and part name 16 is name of the part. The optional part data 21 include quantity (the number) of parts 17, drawing number 18, material 19, and the like, in addition to the above described items.

[0036] Distribution list is part list output as an instruction for supplying parts required for assembling to the working section in each of manufacturing steps to manufacture the robot to be actually manufactured. Fig. 4 shows the example of the image of the distribution list 22 displayed on a display means (liquid crystal panel, monitor, etc) (not shown) included in the production management and acquisition management system. By way of example, the distribution list 22 represents the robot number 23 set as corresponding to the robot to be manufactured and input with the second input means 5, by "0014."

[0037] The distribution list 22 indicates parts for standard equipment and optional parts. A standard portion 24 indicates the parts for standard equipment and an order-receiving portion 25 indicates the optional parts. Therefore, in the part catalog described later which is created using data in the distribution list 22, the parts for standard equipment are distinguishable from

the optional parts. In the distribution list 22, the assortment code 12 is the header number, item code 13 is part number, item name 16 is part name, and required number 17 is quantity (the number) of parts. Instruction number 26 displayed in the distribution list 22 represents the quantity of the parts to be supplied to the working section at the time point when the distribution list 22 is output, and completion number 27 represents the quantity of parts which have been supplied according to the instruction number 26.

[0038] The distribution list is created to include all the parts for standard equipment and optional parts which are required to be assembled into each robot to be manufactured and for each working step. Since the part data stored in the second storage portion 6 of the robot number data creating means 7 in order to output the distribution list has a one to one correspondence with the robot number of the robot to be actually manufactured and delivered to the customer, the part catalog for each robot number can be created based on the part data for each robot number stored in the second storage portion 2.

[0039] Turning back to Fig. 1, the judgment means 8 is included in the system (herein referred to as "sale management system") having a function to read out the part table from the first storage portion 3, select and output items and configuration of the parts to be sold, for the purpose of selling the parts used for manufacturing the robot product to a robot selling company, or a customer for each part, for each assembly, or for each control equipment.

[0040] The judgment means 8 responds to an input signal from the control means 10 that specifies a robot number for which the part catalog is to be created. Based on information relating to all the part configurations forming the robot, and information such as item change of the part associated with design change of the robot product, which is output from the part table creating means 4, and robot number part data from the robot number data creating means 7, the judgment means 8 creates and outputs a part table including only the design change number that coincides with the design change number corresponding to the robot number specified by the input signal, i.e., the parts used for manufacturing the robot for which the part catalog is to be created (the part table thus selected is sometimes referred to as "robot number list 28.") The judgment means 8 is a processing circuit realized by a computer in which a central processing unit (CPU) is mounted.

[0041] In this embodiment, the judgment means 8 creates the robot number list 28 according to the signal from the control means 10, specifying the robot number for which the part catalog is to be created. Alternatively, the judgment means 8 included in the sale management system may be provided with a fourth input means 61 and a fifth storage portion 62. In this configuration, the robot number for which the robot number list 28 is to be created is input with the fourth input means 61 as the

information such as the sale management information, and in accordance with the input signal, the judgment means 8 may create the robot number list 28 and store the robot number list 28 in the fifth storage portion 62. In this case, in accordance with the signal from the control means 10, the robot number list 28 stored in the fifth storage portion 62 is output. The fourth input means 61 is realized by a barcode reader and/or keyboard, and the fifth storage portion 62 is realized by a storage component such as a random access memory, a flash memory, or a hard disc.

[0042] Fig. 5 shows an example of an output of the robot number list 28 as the part table created by the judgment means 8. In the robot number list 28, assortment code 12 is header number, child item code 13 is part number, English name 14 and Japanese name 15 are part names 16, and head count 17 is quantity (the number) of parts. In addition to these, the robot number list 28 includes material 19 to be output.

[0043] The image creating system 9 in Fig. 1 is an illustration creating system configured to create images corresponding to all the parts included in the part table created by the part table creating means 4, so called illustrations, as corresponding to the header numbers.

The image creating system 9 is a processing circuit realized by a computer in which a central processing unit (CPU) is mounted. Also, the image creating system 9 is configured to form an image for each product, for each control equipment, and for each assembly, as well as the image for each part. For example, when a robot number of the robot to be actually manufactured is determined and set, and the robot number is input to the robot number data creating means 7 with the second input means 5, the robot number and an identification number with which group defined for each control equipment and for each assembly is identified, are input. And, the robot number and the group identification number, which have been given to the control means 10 by the robot number data creating means 7, are given to the image creating system 9 by the control means 10, thereby forming the images for each product to be manufactured according to the robot number and the group identification number, and for each control equipment and assembly forming the robot. The illustration creating system as the image creating means 9 is provided with a third storage portion 29 configured to store image data of the respective parts created as corresponding to the header numbers, image data of the product, image data of the control equipment and image data of the assembly.

[0044] The control means 10 is a processing circuit realized by a computer in which a central processing unit (CPU) is mounted. The third input means 30, the judgment means 8, and the image creating means 9 are connected to the control means 10, and the output of the control means 10 is given to the display means 32 and the storage means 33. In addition, the control means 10 is provided with a fourth storage portion 31 in which the

part catalog data is stored. Herein, a section comprising the control means 10, the third input means 30, the display means 32, the storage means 33, and the fourth storage portion 31 and having a function to create and output the part catalog data is called a part catalog automatic creating system 34.

[0045] The third input means 30 is realized by a key board or the like. With the third input means 30, the robot number for which the part catalog is to be created is selected and is input to the control means 10. In response to the input signal from the third input means 30 that specifies the robot number, the control means 10 takes in the robot number list 28 corresponding to the specified robot number from the judgment means 8. Also, the control means 10 takes in the image data of each part with the header number corresponding to the robot number list 28 set, from the image creating system 9 or from the third storage portion 29 included in the image creating system 9. The control means 10 combine these image data to create the part catalog data for each robot number. The created part catalog data is output to one of or both of the display means 32 and the storage means 33 by the control means 10 and are stored in the fourth storage portion 31.

[0046] The display means 32 is realized by a liquid crystal display panel or a cathode ray tube. The storage means 33 comprises a printer and a recorder. The storage means 33 is configured to store the part catalog data in one of or both of the paper 36 and an electric medium 37 as external storage media 35 and create the part catalog. The electronic medium 37 may be, for example, a flexible disc (FD) by magnetic storage, or may be, for example, a compact disc (CD-R) by optical storage. The part catalog is offered in one or a plurality of forms selected from the paper, the FD, the CD-R, and the like.

[0047] The storage medium that contains the part catalog is offered to the customer together with, for example, the robot product. The storage medium given to the customer inhibits the customer from confusing the robot listed in the part catalog with the robot delivered to the customer, and the customer can easily specify and order required parts with reference to the part catalog corresponding to the delivered robot. Further, by storing the part catalog delivered together with the robot in a storage portion provided in the robot, missing of the part catalog can be avoided, and information relating to maintenance of the robot or the like can be easily obtained from the stored part catalog.

[0048] Fig. 6 is a view showing an example of the image of the part catalog illustrating an apparatus construction of the robot. Fig. 7 is a view showing an example of a content list portion 48 of the part catalog associated with each assembly of the robot. Fig. 8 is a view showing an example of the part catalog of the parts forming the assembly of the robot.

[0049] Figs. 6 to 8 illustrate the part catalog output onto the paper 36. Fig. 6 shows a construction of an ap-

paratus called an arm portion 41 of the robot. As shown in Fig. 6, the arm portion 41 is composed of assemblies called units, i.e., an upper arm unit 42, a lower arm unit 43, a link unit 44, a list unit 45, a balancer unit 46, and a base unit 47.

[0050] The units 42 to 47 are each composed of assemblies in a lower layer, and the part catalogs are created for each of the assemblies. The part catalog for each assembly is illustrated in such a manner that the image and page of the assembly are displayed in the content list portion 48 in Fig. 8. For example, the part catalog relating to an assembly called "lower arm 3" is illustrated as listed on page 15 of the content list portion 48. On page 15, a part catalog 49 of the "lower arm 3" shown in Fig. 8 is found.

[0051] An image portion 50 of the part catalog 49 of the "lower arm 3" in Fig. 8 displays header number "P018" representing a clamp duct as one part of the "lower arm 3" as indicated by a reference numeral 51. The header number 51 represents that a shape of the clamp duct is an image (illustration) 53 indicated by a drawing line 52. Meanwhile, on a list portion 54 of the part catalog 49 of the "lower arm 3," the header number is displayed on the column of "No." On a line of the header number 51 "P018" on the list portion 54, part number "60373 - 1221", part name "clamp duct 2", and quantity of parts "2" are displayed.

[0052] Figs. 6 to 8 show the part catalog obtained by outputting the part catalog data to the paper 36 (Fig. 1) of the storage means 33 by the control means 10. In the same manner, the part catalog data can be output to, for example, the display means 32 comprised of the liquid crystal panel. When the part catalog is displayed on the display means 32, the display means 32 is provided with a function in which link is formed between an image and a display portion on the image which are associated with each other by the header number, and free movement between images and between display portions on the image, is performed in accordance with an operation to select a hot spot formed on the image ("function similar to "hyperlink"). For example, among the image representing the configuration of the control equipment of the arm portion 41 in Fig. 6, the image of the content list portion 48 in Fig. 7, and the image of the part catalog 49 of the "lower arm 3" in Fig. 8, free movement is carried out by using a mouse or the like as the input means provided in the display means 32 to select the hot spot.

[0053] Fig. 9 is a flowchart for explaining operations for creating the part catalog in the part catalog creating system 1. A series of operations for creating the part catalog for each robot number of the robot product by the part catalog creating system 1 will be described with reference to a flowchart in Fig. 9.

[0054] In step s1, with the first input means 2, a design change number set as corresponding to each of the parts used for manufacturing the robot product, header number, part number, part name, and quantity (the number) of parts required to be assembled into the robot

product, each of which corresponds to the design change number, are input to the part table creating means 4. In step s2, the part table that contains the design change number, the header number, the part number, the part name, and the quantity of parts is stored in the first storage portion 3. In Step s3, the image creating means 9 creates an image (illustration) of each part corresponding to the header number. The created image of each part is stored in the third storage portion 29.

[0055] In Step s4, with the second input means 5, a robot number of a robot product and design change number of the part for standard equipment and optional part, which are used in the robot of the robot number, are input to the robot number data creating means 7. In Step s5, the robot number of the robot product and the design change number of the part corresponding to the robot number, which correspond to the input robot number data, are stored in the second storage portion 6.

[0056] In Step s6, the judgment means 8 compares the design change number in the part table which has been read out from the first storage portion 3 to the design change number corresponding to the robot number which has been read out from the second storage portion 6. In Step s7, the judgment means 8 selects only the design change number corresponding to the robot number which has been read out from the second storage portion 6, from the part table, and removes the remaining design change number which have not been selected, and header numbers, part numbers, and the like, which correspond to the remaining design change numbers, from the part table.

[0057] In Step s8, the control means 10 takes in the image of the part that coincides with the header number corresponding to the robot number which has been read out from the second storage portion 6. In step s9, the control means 10 combines the selected part table and the taken-in image, thereby creating the part catalog data. In step s10, the control means 10 outputs the part catalog data to be stored in the storage means 33 and creates the part catalog.

[0058] In Step s11, it is judged whether or not the part catalog of a subsequent robot number should be created. When it is judged that the part catalog of the subsequent robot number should be created, processing returns to Step s4, and the following steps are performed. When it is judged that the part catalog of the subsequent robot number should not be created, the series of operations for creating the part catalog is completed.

[0059] The above described series of operations are for the case where the part table and the part catalog for each robot number are newly created. Operations for creating the part catalog for each robot number in the case where the created part table is stored in the first storage portion 3, various robot-number products have been already manufactured, and the robot number data for numerous robot-number products are stored in the second storage portion 6, will be described below.

[0060] First of all, with the third input means 30 (Fig. 1), the robot number for which the part catalog is to be created is selected and input to the control means 10. The control mean 10 outputs a signal for specifying the robot number to the judgment means 8. The judgment means 8 responds to the signal for specifying the robot number and starts the operation in step s6. The Step s6 and the following steps sequentially advance along the steps shown in the flowchart in Fig. 9. When it is judged that the part catalog of a subsequent robot number should be created in step s11, the robot number for which a subsequent part catalog is to be created is input to the control means 10 with the third input means 30, and the above described operation is repeated. When it is judged that the subsequent part catalog should not be created, the series of operations for creating the part catalog is completed.

[0061] As described above, the part table of the robot product is created, the robot number data creating means 7 specifies the parts used for the robot to be manufactured, and the judgment means 8 selects the parts from the part table and creates the robot number list 28 in accordance with the specification by the robot number data creating means 7. The control means 10 combines the robot number list 28 and the images of the parts corresponding to the header numbers in the robot number list 28 and creates the part catalog.

[0062] As should be appreciated from the forgoing, in contrast to a case where the parts used for the robot to be manufactured are manually selected from the part table, mistakes in selection and errors in posting can be avoided and the parts can be selected without manual labor. Therefore, it is possible to significantly reduce the labor required for creating the part catalog, and create the part catalog having a one to one correspondence with the robot number of the product. In addition, the part table is rewritable and when the parts used for manufacture are changed according to design change, the data in the part table creating means 4 is rewritten with the first input means 2. Thereby, the part table can be easily updated and the part catalog based on the part table can be updated. As a result, the part table is inhibited from becoming obsolete.

[0063] Fig. 10 is a view showing a simplified configuration of a part catalog creating system 55 according to a second embodiment of the present invention. The part catalog creating system 55 of this embodiment is similar to the part catalog creating system 1 of the first embodiment, and in Fig. 10, the same reference numerals as those in Fig. 1 denote the same or corresponding parts, which will not be further described. It should be noted that the part catalog creating system 55 further comprises a communication means 56 configured to transmit the part catalog data output from the control means 10 through a communication network.

[0064] The control means 10 of the part catalog creating system 55 is connected to a public phone line 57 through a communication modem or the like, and the

public phone line 57 is connected to a network search access system 58 in Fig. 10, thereby enabling communication. The network search access system 58 is realized by, for example, Internet. The communication modem, the public phone line 57, and the network search access system 58 realized by the Internet configure the communication means 56.

[0065] The customer and the selling company that can search and access to the part catalog comprise terminals 59a, 59b, and 59c for search and access and communication modems (including communication equipment such as routers). The terminals 59a, 59b, and 59c are connected to public phone lines 60a, 60b, and 60c through the communication modems, respectively. Since the public phone lines 60a, 60b, and 60c are connected to the network search access system 58, the customer, the selling company, and the like can search and access to the part catalog for each robot number which is output from the control means 10 or the part catalog for each robot number which is stored in the fourth storage portion 31.

[0066] By configuring so that the part catalog data for each robot number of the product which is output from the control means 10 through the communication means including a communication network such as the public phone line, the customer, the selling company and the like can search and access to the part catalog for each robot number of the product which is transmitted though the communication means by using the terminals connected to the communication network. Thereby, newest catalog data is easily accessible even in a remote place.

Industrial Applicability

[0067] In accordance with the present invention, it is possible to create part catalogs having a one to one correspondence with a robot number of a product correctly and without much labor, for products such as robot products which are composed of numerous parts, have a variety of part configurations according to customers' requirements, and are designed in short cycles.

Claims

1. A part catalog creating system comprising:

(a) a part table creating means including a first storage portion configured to store a part table to be rewritable, the part table containing design change numbers respectively set for a plurality of parts composing a product obtained by assembling the plurality of parts and information corresponding to the design change numbers;

(b) a product number data creating means including a second storage portion configured to

store product number data containing design change numbers and information of parts used for each of product numbers of a product assembled with different part configurations so as to correspond to the product numbers;

(c) a judgment means configured to compare a design change number of the product number data of the product that has been read out from the second storage portion to a design change number of the part table that has been read out from the first storage portion, select the design change number of the part table that coincides with the design change number that has been read out from the second storage portion, and remove design change numbers remaining unselected and information corresponding to the unselected design change numbers from the part table; and

(d) a control means configured to create part catalog data for each product number of the product from the part table that contains the information corresponding to the design change number selected by the judgment means, and to output the part catalog data.

2. The part catalog creating system according to Claim 1, further comprising:

an image creating means configured to create an image corresponding to the design change number selected by the judgment means, wherein

the control means is configured to create the part catalog data for each product number of the product, from the image created by the image creating means and the part table containing the design change number selected by the judgment means and information corresponding to the design change number, and to output the part catalog data.

3. The part catalog creating system according to Claim 1, wherein

the information corresponding to the design change numbers which are stored in the first storage portion of the part table creating means include header numbers, part numbers, and quantity of parts required to be assembled into the product,

the information stored in the second storage portion of the product number data creating means include design change numbers of parts used for each product number of the product, header numbers of the parts, part numbers of the parts, and quantity of the parts required to be assembled into the product, and

the information corresponding to the unselected design change numbers removed from the part table by the judgment means include header

numbers, part numbers, and the quantity of parts required to be assembled into the product.

4. The part catalog creating system according to Claim 2, wherein the part catalog data output by the control means includes a part name corresponding to the design change number. 5
5. The part catalog creating system according to Claim 3, wherein the control means creates the part catalog data for each product number of the product from the part table that contains the design change number selected by the judgment means, the part number and the quantity of the parts required to be assembled into the product, each of which corresponds to the design change number, and outputs the part catalog data in such a manner that parts for standard equipment are distinguished from optional parts. 10 15 20
6. The part catalog creating system according to Claim 1, further comprising:
a communication means configured to transmit the part catalog data output from the control means through a communication network, wherein the part catalog is searchable and accessible through the communication means. 25 30
7. The part catalog creating system according to Claim 1, wherein the part catalog data output from the control means is stored in an external storage medium to allow the part catalog to be delivered. 35

40

45

50

55




Fig. 1

SPECIFIED ITEM LEVEL	ITEM ASSORTMENT	ITEM CODE	ITEM NAME (ENGLISH)	ITEM NAME (JAPANESE)	HEAD COUNT UNIT	DRAWING NUMBER	NUMBER OF DRAWINGS	PRODUCT	MATERIAL	STANDARD
32X130U-1.....	UB	A	40911-1095	WRIST-UNIT	1 ST	60320-1123C	D	ZX130S/165U		
32X130U-2.....	UP	A	60320-1123	HOUSING-HAND 1	1 PC	61320-1123C	D	ZX130/165	FCD450	
32X130U-3.....	RM	A	61320-1123	HOUSING-RM, HAND 1	1 PC	60320-1124B	D	ZX130/165	FCD450	
32X130U-2.....	UP	A	60320-1124	HOUSING-HAND 2	1 PC	61320-1124B	D	ZX130/165	FCD450	
32X130U-3.....	RM	A	61320-1124	HOUSING-RM, HAND 2	1 PC	60210-1212C	C	ZX130/165	SCM415-N	
32X130U-2.....	UP	A	60210-1212	GEAR-SPUR, JT6-3	1 PC	60210-1213C	C	ZX130/165	SCM415-N	
32X130U-2.....	UP	A	60210-1213	GEAR-SPUR, JT6-4	1 PC	60212-1136A	C	ZX130/165/200	SCM415-N	
32X130U-2.....	UP	A	60212-1136	GEAR-BEVEL, JT5-1	1 PC	60212-1137A	B	ZX130/165	SCM415-N	
32X130U-2.....	UP	A	60212-1137	GEAR-BEVEL, JT5-2	1 PC	60212-1138A	B	ZX130/165/200	SCM415-N	
32X130U-2.....	UP	A	60212-1138	GEAR-BEVEL, JT6-1	1 PC	60212-1139A	C	ZX130/165/200	SCM415-N	
32X130U-2.....	UP	A	60212-1139	GEAR-BEVEL, JT6-2	1 PC	60212-1140A	C	ZX130/165	SCM415-N	
32X130U-2.....	UP	A	60212-1140	GEAR-BEVEL, JT6-3	1 PC	60212-1141A	B	ZX130/165	SCM415-N	
32X130U-2.....	UP	A	60212-1141	GEAR-BEVEL, JT6-4	1 PC	60124-1218A	B	ZX130/165	SS400	
32X130U-2.....	UP	A	60124-1218	RETAINER, BEARING JT	2 PC	60132-1062A	A	ZX130/165/200	S45C-H	
32X130U-2.....	UP	A	60132-1062	RING, JT5	1 PC	60132-1062A	A	ZX130/165	..	
..	
..	

Fig. 2

21

12

ITEM ASSORTMENT

18

19

ESTIMATED COST

17

PRODUCT CODE: G SPARE (UNIT)

2001/08/07

PUBLICATION DATE

W/O	WORK ITEMIZE	START	END	ASSORTMENT CODE	PART NUMBER	PART NAME	16	DRAWING NUMBER	MATERIAL	PECIFICATION STANDARD	QUANTITY	UNIT
Z 8102003	NP01	1	1	SP01	50480-1006	HAND ASSY, 200 MAIN - A	SA	50480-1006D			0.00	ST
Z 8102003	NP02	1	1	SP02	50480-1023	HAND ASSY, 300 MAIN - B	SA	50480-1023A			0.00	ST
Z 8102003	NP03	1	1	SP03	50480-1041	HAND ASSY, 200 - A MAINTENANCE	SA	50480-1041A			0.00	ST
Z 8102003	NP04	1	1	SP04	40912-1054	ARM UNIT, X	UB	40912-1054A			0.00	ST
Z 8102003	NP05	1	1	SP05	40912-1057	ARM UNIT, X (300)	UB	40912-1057A			0.00	ST
Z 8102003	NP06	1	1	SP06	40921-1011	ROTOR UNIT, SHEETER	UB	40921-1011A			0.00	ST
Z 8102003	NP07	1	1	SP07	40912-1064	ARM UNIT, X - TH-311	UB	40912-1064B			0.00	ST
Z 8102003	NP08	1	1	SP08	60375-1831	COVER, HOUSING 1	UP	60375-1831A	A2017		0.00	PC
Z 8102003	NP09	1	1	SP09	60375-1829	COVER, HOUSING 2	UP	60375-1829A	A2017		0.00	PC
Z 8102003	NP10	1	1	SP10	60375-1830	COVER, HOUSING 3	UP	60375-1830A	ACRYL (TRANSPARENT)		0.00	PC
Z 8102003	NP11	1	1	SP11	50581-1009	SENSOR ASSY (KINAI), BEAM	UP		PURCHASE		0.00	ST
Z 8102003	NP12	1	1	SP12	PPFN38U	MACHINE SCREW, BRASS	UP	PRO503	SUS304	PF-M2-8	0.00	PC
Z 8102003	NP13	1	1	SP13	PSB24U	HEXAGON SOCKET HEAD CAP SCREW	UP	SUS304	SB-M2-4		0.00	PC
Z 8102003	NP14	1	1	SP14	50975-3708	HARNES ASSY (KINAI), S5	SA	50975-3708C		S5 HARNES ASSY	0.00	ST
Z 8102003	NP15	1	1	SP15	40912-1062	ARM UNIT, X-TH-311004	UB	40912-1062B			0.00	ST
Z 8102003	NP16	1	1	SP16	60375-1788	COVER, HOUSING 1	UP	60375-1788B	A5052		0.00	PC
Z 8102003	NP17	1	1	SP17	60375-1789	COVER, HOUSING 2	UP	60375-1789A	A5052		0.00	PC
Z 8102003	NP18	1	1	SP18	PPFN06U	MACHINE SCREW BRASS (SUS)	UP	PRO503	SUS304	PF-M3-6	0.00	PC
Z 8102003	NP19	1	1	SP19	50975-3708	HARNES ASSY (KINAI), S5	SA	50975-3708C		S5 HARNES ASSY	0.00	ST
Z 8102003	NP20	1	1	SP20	40580-1007	SENSOR UNIT, 200 MAIN - B	UB	40580-1007A			0.00	ST
Z 8102003	NP21	1	1	SP21	40580-1009	SENSOR UNIT, 300 MAIN - B	UB	40580-1009B			0.00	ST

Fig. 3

PROCESS MENU
FOET02-DETAIL OF DUE-OUT
01/09/14 10:40:51
UNIT

WORK No. INVENTORY W/O SEQ PRODUCT CODE ROOT NUMBER STEP NAME WORKA COMPLETION WORK COMPLETION INSTRUCTION
152579 8153982 Z1185UEC32002_0014 MECHANICAL ASSEMBY 01/04/18 01/04/18 01/04/18

STANDARD PORTION

DISTRIBUTION DESTINATION	ASSIGNMENT CODE	ITEM NAME	ITEM NUMBER	MANUFACTURE TYPE	STORAGE SITE	REQUIRED NUMBER	INSTRUCTION NUMBER	COMPLETION NUMBER
Q 202	Q0RBC115X	O-RING	K25004C		01-18	1		27
K 203	Q0RBC120X	O-RING	K25004C		01-01	1		26
A 208	Q0P18U	PT FLOATING PLUG	K08008R		01-37	1		27
K 212	Q0P18U	PT FLOATING PLUG	K08008R		01-37	1		26
Q 205	Q0P18U	PT FLOATING PLUG	K08008R		01-37	2		27
A 221	Q0P1037C	PARALLEL PIN	K10400A		A0133	1		27
A 211	Q0P255C	PARALLEL PIN	K10400A		A0124	1		26
K 349	Q0R24	EYE BOLT	K0800DA		A014	3		27
K 211	Q0M18	GREASE NIPPLE	K15010A		08-05	1		26
K 212	Q0M18	GREASE NIPPLE	K15010A		08-05	1		27

CODE RECEIVING PORTION

DISTRIBUTION DESTINATION	ASSIGNMENT CODE	ITEM NAME	ITEM NUMBER	MANUFACTURE TYPE	STORAGE SITE	REQUIRED NUMBER	INSTRUCTION NUMBER	COMPLETION NUMBER
ADP102	Q0P1022C	PARALLEL PIN	K10400A		08-14	0		27
ADP101	Q0R41015	PARALLEL PIN	K01000A		F0071	0		27
S11102	Q0R41015	PARALLEL PIN	K01000A		94-32	2		27
L11108	Q0R41015	PARALLEL PIN	K01000A		F0083	2		27
S11101	Q0R41015	PARALLEL PIN	K01000A		F0085	4		27
L11103	Q0R41015	PARALLEL PIN	K01000A		F0085	4		27
CON105	Q0R41015	PARALLEL PIN	K01000A		F0085	4		27

START EXPLORER RUMCS Microsoft Excel - Book1 1054

Fig. 4

PARENT ITEM CODE LEVEL	ASSORTMENT CODE	CHILD ITEM CODE	DRAWING NUMBER	ENGLISH NAME	JAPANESE NAME	UNIT	HEAD COUNT	MATERIAL	SPECIFICATION
3ZX130U-	1 A	40911-1095		WRIST-UNIT	WRIST-UNIT	ST	1		
3ZX130U-	2 A 001	60320-1123	60320-1123C	HOUSING,HAND 1	HOUSING, HAND 1	PC	1	FCD450	
3ZX130U-	3	61320-1123	61320-1123C	HOUSING-RM,HAND 1	HOUSING-RM, HAND 1	PC	1	FCD450	
3ZX130U-	2 A 002	60320-1124	60320-1124B	HOUSING,HAND 2	HOUSING, HAND 2	PC	1	FCD450	
3ZX130U-	3	61320-1124	61320-1124B	HOUSING-RM,HAND 2	HOUSING-RM, HAND 2	PC	1	FCD450	
3ZX130U-	2 A 007	60210-1212	60210-1212C	GEAR-SPUR, JT6-3	GEAR-SPUR, JT6-3	PC	1	SCM415-N	
3ZX130U-	2 A 008	60210-1213	60210-1213C	GEAR-SPUR, JT6-4	GEAR-SPUR, JT6-4	PC	1	SCM415-N	
3ZX130U-	2 A 009	60212-1136	60212-1136A	GEAR-BEVEL, JT5-1	GEAR-BEVEL, JT5-1	PC	1	SCM415-N	
3ZX130U-	2 A 010	60212-1137	60212-1137A	GEAR-BEVEL, JT5-2	GEAR-BEVEL, JT5-2	PC	1	SCM415-N	
3ZX130U-	2 A 011	60212-1138	60212-1138A	GEAR-BEVEL, JT6-1	GEAR-BEVEL, JT6-1	PC	1	SCM415-N	
3ZX130U-	2 A 012	60212-1139	60212-1139A	GEAR-BEVEL, JT6-2	GEAR-BEVEL, JT6-2	PC	1	SCM415-N	
3ZX130U-	2 A 013	60212-1140	60212-1140A	GEAR-BEVEL, JT6-3	GEAR-BEVEL, JT6-3	PC	1	SCM415-N	
3ZX130U-	2 A 014	60212-1141	60212-1141A	GEAR-BEVEL, JT6-4	GEAR-BEVEL, JT6-4	PC	1	SCM415-N	
3ZX130U-	2 A 015	60124-1218	60124-1218A	RETAINER, BEARING JT6	RETAINER, BEARING JT6	PC	2	SS400	
3ZX130U-	2 A 016	60132-1062	60132-1062A	RING, JT5	RING JT5	PC	1	S45C-H	
:	:	:	:	:	:	:	:	:	:
:	:	:	:	:	:	:	:	:	:

Fig. 5




Fig. 6

CONTENT LIST ← 48

ZX130U-A002





Fig. 7






Fig. 9




Fig. 10

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP02/11081

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl ⁷ G06F17/50, G06F17/60		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) Int.Cl ⁷ G06F17/50, G06F17/60		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 00/13115 A1 (DAIMLER-CHRYSLER AG.), 09 March, 2000 (09.03.00), Full text; all drawings & JP 2002-523840 A	1-7
A	JP 2001-282343 A (Fujitsu Ltd.), 12 October, 2001 (12.10.01), Full text; all drawings (Family: none)	1-7
A	JP 6-162036 A (Fujitsu Ltd.), 10 June, 1994 (10.06.94), Full text; all drawings & US 5579231 A	1-7
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 13 November, 2002 (13.11.02)		Date of mailing of the international search report 26 November, 2002 (26.11.02)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1998)